

Type.....	57680
Designation.....	Eco Charger
Systems to charge.....	Ni-Mh
Cell configurations.....	1 – 4 pcs; AAA, AA
Housing Material:.....	50 % Biomass 50 % PP
Casing colour:.....	Black
Dimensions:	Charger:
Length.....	108 mm
Width.....	76 mm
Height.....	28 mm
Weight.....	91 g



Charging methods:	USB 5 V 500 mA or 2100 mA	Maintenance Charge 1 hr:
AA 1 – 2 pcs.	Current: 500 mA or 1400 mA	Current: 100 mA
AA 3 – 4 pcs.	Current: 250 mA or 700 mA	Current: 100 mA
AAA 1 – 4 pcs.	Current: 250 mA or 700 mA	Current: 50 mA
AA/AAA	Current: 250 mA or 700 mA	Current: 50 mA

Indications for LED Display:	2 per slot, 8 total
AA, AAA, cell mix:	Charging <50 % SoC: left blink, right off
	Charging >50 % <100 % SoC: left on, right blink
	Charging complete 100 % SoC: left on, right on
	Fault (any): left blink, right blink

Protective Functions: Reverse protection
Short circuit protection
Mechanical arrangement
function normally, when removal of short circuit

Power: Primary USB 5 V 500 mA or 2100 mA
Secondary 1.4 V

Cut off criteria: Timer: backup timer
Minus delta V detection

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries