

| | |
|--|----------------------------------|
| Type..... | 57965 |
| Designation..... | Slim Power Bank 6000 |
| Systems to charge..... | Lithium-Polymer / 3.7 V / 1 pcs. |
| Cell configurations..... | 6000 mAh, 22.2 Wh |
| Housing Material: Aluminium | |
| Casing colour: | Brushed silver |
| Cover colour: | Black |
| Dimensions: | |
| Length..... | 142 +- 1 mm |
| Width..... | 71 +- 1 mm |
| Height..... | 12 +- 1mm |
| Weight..... | 192 g |



| | | |
|-----------------------------|--|----------------------------|
| Charging methods: | Plug in Micro USB and USB Type C port: | Maintenance Charge: |
| Input 1: Micro USB..... | Current: 2000 mA | N/A |
| Input 2: USB Type C..... | Current: 3000 mA | |
| Discharging methods: | USB A and Type C port for charging other devices: | |
| Output1: USB A..... | 5 V, 2400 mA | |
| Output2: USB Type C..... | 5 V, 3000 mA | |

Indications for LED Display:

| | | |
|----------------------------------|------------|----------|
| Charging: | | |
| LED 1 flashing..... | 0 - 25 % | Capacity |
| LED 1 on LED 2 flashing..... | 25 - 50 % | Capacity |
| LED 1 - 2 on LED 3 flashing..... | 50 - 75 % | Capacity |
| LED 1 - 3 on LED 4 flashing..... | 75 - 99 % | Capacity |
| LED 1 - 4 solid on..... | 100 % | Capacity |
| Discharging: | | |
| 4 Blue LED | 100 - 76 % | Capacity |
| 3 Blue LED | 51 - 75 % | Capacity |
| 2 Blue LED | 26 - 50 % | Capacity |
| 1 Blue LED | 3 - 25 % | Capacity |
| 1 flashing Blue LED | <3 % | Capacity |

| | |
|-----------------------------|--------------|
| Ambient temperature: | |
| Charge..... | 0 - +45 °C |
| Discharge..... | -20 - +45 °C |
| Storage..... | -20 - +45 °C |

| | |
|--------------------------|--|
| Cut off criteria: | |
| Li-Ion cells..... | Stop discharging, when Li-Polymer voltage lower than 2.8 V |
| | Short circuit protection |
| | Overload protection |

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries