



## LIGHT STICK

Lampada da lavoro ricaricabile 3W COB LED  
 3W LED COB Rechargeable worklight  
 Baladeuse rechargeable 3W COB LED  
 Lámpara para taller recargable 3W COB LED  
 Wiederaufladbare LED-Werkstattlampe



INCLUSI/INCLUDED/INCLUS/INCLUIDOS/INBEGRIFFEN



IS575



PACKING	INNER	MASTER
/	pcs	pcs
Blister F8	6	24



### DATI TECNICI / SPECIFICATION / CARACTÉRISTIQUES / CARACTERISTICAS / SPEZIFIKATIONEN

Codice / Item / Code / Codigo / Code	IS575
Nome prodotto / product name / Nom du produit / Designación / Produktname	LIGHT STICK
Alimentazione / Power supply / Alimentation / Alimentación / Stromversorgung	12V --- 500mA
Batteria / Battery / Batterie/ Batería / Batterie	3.7V 1800mA Li-ion (Included) type 18650
Tempo di ricarica / Charging Time / Temps de recharge / Tiempo de carga / Ladezeit	4 hrs
Autonomia / Runtime / Autonomie / Autonomía / Leuchtdauer	High: 3 hrs - Low: 9 hrs
Tecnologia della Luce / Light technology / Technologie de la lumière / Tecnología de iluminación / Leuchtentechnologie	COB LED
Potenza d'illuminazione (W) / (W) Power / Puissance (W) / Potencia (W) / Leuchtstärke (W)	3W
Consumo elettrico (W) / (W) Consumption / Consommation (W) / Consumo (W) / Verbrauch (W)	
Lumen / Lumen / Lumen / Lumen / Lumen	250 Lm
Tipo di luce / Kelvin degrees / Degrés Kelvin / Temperatura de luz / Grad Kelvin	6500K
IRC / Colour rendering Index / Indice de rendu des couleurs / IRC / Farbwiedergabeindex	
Fascio di luce / Light beam / Type de faisceau / Tipo de haz / Lichtstrahl	120°
Portata / Range / Distance d'éclairage / Alcance alumbrado / Leuchtweite	5 mt
Durata di vita del LED / LED Life time / Durée de vie des LED / Durada de vida del LED / Lebensdauer LED	
Massima intensità del fascio / Peak beam intensity / Intensité maximale du faisceau / Máxima intensidad / Abstrahlintensität	
Dimmerabilità / Dimmable / Dimmable / Dimmer, regulador / Dimmereigenschaften	YES (100% / 50%)
Numero di cicli on-off / On off cycles / Nr de cycles on-off / Numero de On-OFF / Ein-Aus Zyklen	
Power factor / Power factor / Power factor / Power factor / Leistungsfaktor	
Cavo / Cable / Câble / Cable / Kabel	
Materiale / Material / Matériau / Material / Material	ABS
Grado di protezione / Protection degree / Degré de protection / Estanqueidad / Schutzgrad	IP20
Resistenza Meccanica / Mechanical resistance / Résistance Mécanique / Resistencia mecanica / Mechanische Widerstandsfähigkeit	
Accessori inclusi / Accessories included / Accessoires fournis / Accesorios incluidos / Zubehör enthalten	220V adaptor, 12V adaptor, Magnet, Hook
Funzioni / Functions / Fonctions / Función / Funktionen	100%-50%
Dimensioni prodotto / Product dimensions / Dimensions du produit / Dimensiones producto / Abmessungen Produkt	Width x Height x Length: 57 x 50 x 410 mm
Dimensioni prodotto imballato / Packed dimensions / Dimensions du produit emballé / Dimensiones embalaje / Abmessungen Umverpackung	Width x Height x Length: 156 x 87 x 443 mm
Peso netto / Net Weight / Poids net / Peso neto / Gewicht netto	405 g
Peso prodotto imballato / Weight of packaged product / Poids du produit emballé / Peso producto con embalaje / Gewicht mit Umverpackung	450 g