



Driver

PADLIGHT-3

Faro LED da esterno
LED outdoor floodlight
Phare extérieur LED
Faro exterior de LED
Flutlicht für Außenbereiche



IS748-3-6500K



PACKING	INNER	MASTER
	pcs	pcs
Colour box	8	8

DATI TECNICI / SPECIFICATION / CARACTÉRISTIQUES / CARACTERISTICAS / SPEZIFIKATIONEN

Codice / Item / Code / Código / Code	IS748-3-6500K
Nome prodotto / product name / Nom du produit / Designación / Produktname	PADLIGHT-3 20W + PIR
Alimentazione / Power supply / Alimentation / Alimentación / Stromversorgung	220-240V ~ 50 Hz
Tecnologia della Luce / Light technology / Technologie de la lumière / Tecnología de iluminación / Leuchten-technologie	2835 SMD LED
Potenza d'illuminazione (W) / (W) Power / Puissance (W) / Potencia (W) / Leuchtstärke (W)	20W
Consumo elettrico (W) / (W) Consumption / Consommation (W) / Consumo (W) / Verbrauch (W)	20W
Lumen / Lumen / Lumen / Lumen / Lumen	1600 Lm
Tipo di luce / Kelvin degrees / Degrés Kelvin / Temperatura de luz / Grad Kelvin	6500K
IRC / Colour rendering Index / Indice de rendu des couleurs / IRC / Farbwiedergabeindex	>65 Ra
Fascio di luce / Light beam / Type de faisceau / Tipo de haz / Lichtstrahl	Diffuse 100°
Durata di vita del LED / LED Life time / Durée de vie des LED / Durada de vida del LED / Lebensdauer LED	25.000 hrs
Dimmerabilità / Dimmable / Dimmable / Dimmer, regulador / Dimmereigenschaften	NO
Numero di cicli on-off / On off cycles / Nr de cycles on-off / Numero de On-OFF / Ein-Aus Zyklen	15.000
Power factor / Power factor / Power factor / Power factor / Leistungsfaktor	>0,9
Materiale / Material / Matériau / Material / Material	Die-cast Aluminium
Angolo di rilevazione / Degrees motion sensor/ Angle / Grados de sensor / Erfassungswinkel	100°
Raggio d'azione / Detection range / Rayon d'action / Rayo de acción / Reichweite	12 m
Sensibilità luminosa minima / Minimum ambient light / Sensibilité lumineuse minimale / Sensibilidad luminosa mínima / Mindestlichtempfindlichkeit	10-2000 Lux
Tempo di funzionamento / Working time / Temps de fonctionnement / Tiempo de funcionamiento / Betriebszeit	from 10 sec up to 10 min approx
Grado di protezione / Protection degree / Degré de protection / Estanqueidad / Schutzgrad	IP44
Accessori inclusi / Accessories included / Accessoires fourni / Accesorios incluidos / Zubehör enthalten	EASY CONNECTION
Dimensioni prodotto / Product dimensions / Dimensions du produit / Dimensiones producto / Abmessungen Produkt	Width x Height x Length: 144 x 70 x 195 mm
Dimensioni prodotto imballato / Packed dimensions / Dimensions du produit emballé / Dimensiones embalaje / Abmessungen Umverpackung	Width x Height x Length: 150 x 77 x 205 mm
Peso netto / Net Weight / Poids net / Peso neto / Gewicht netto	500 g
Peso prodotto imballato / Weight of packaged product / Poids du produit emballé / Peso producto con embalaje / Gewicht mit Umverpackung	599 g