



PADLIGHT-3

Faro LED da esterno
LED outdoor floodlight
Phare extérieur LED
Faro exterior de LED
Flutlicht für Außenbereiche



WATER RESISTANT ✓
EASY CONNECTION ✓
SAFE ✓



IS760-3-4000K



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	6	6



DATI TECNICI / SPECIFICATION / CARACTÉRISTIQUES / CARACTERISTICAS / SPEZIFIKATIONEN

Codice / Item / Code / Código / Code	IS760-3-4000K
Nome prodotto / product name / Nom du produit / Designación / Produktname	PADLIGHT-3 50W
Alimentazione / Power supply / Alimentation / Alimentación / Stromversorgung	220-240V ~ 50 Hz
Batteria / Battery / Batterie/ Bateria / Batterie	-
Tempo di ricarica / Charging Time / Temps de recharge / Tiempo de carga / Ladezeit	-
Autonomia / Runtime / Autonomie / Autonomía / Leuchtdauer	-
Tecnologia della Luce / Light technology / Technologie de la lumière / Tecnología de iluminación / Leuchtentechnologie	2835 SMD LED
Potenza d'illuminazione (W) / (W) Power / Puissance (W) / Potencia (W) / Leuchtstärke (W)	50W
Consumo elettrico (W) / (W) Consumption / Consommation (W) / Consumo (W) / Verbrauch (W)	50W
Lumen / Lumen / Lumen / Lumen / Lumen	4000 Lm
Tipo di luce / Kelvin degrees / Degrés Kelvin / Temperatura de luz / Grad Kelvin	4000K
IRC / Colour rendering Index / Indice de rendu des couleurs / IRC / Farbwiedergabeindex	>65 Ra
Fascio di luce / Light beam / Type de faisceau / Tipo de haz / Lichtstrahl	Diffuse 100°
Portata / Range / Distance d'éclairage / Alcance alumbrado / Leuchtweite	-
Durata di vita del LED / LED Life time / Durée de vie des LED / Durada de vida del LED / Lebensdauer LED	25.000 hrs
Massima intensità del fascio / Peak beam intensity / Intensité maximale du faisceau / Máxima intensidad / Abstrahlintensität	-
Dimmerabilità / Dimmable / Dimmable / Dimmer, regulador / Dimmereigenschaften	NO
Numero di cicli on-off / On off cycles / Nr de cycles on-off / Numero de On-OFF / Ein-Aus Zyklen	15.000
Power factor / Power factor / Power factor / Power factor / Leistungsfaktor	>0,9
Cavo / Cable / Câble / Cable / Kabel	-
Materiale / Material / Materiau / Material / Material	Die-cast Aluminium
Grado di protezione / Protection degree / Degré de protection / Estanqueidad / Schutzgrad	IP65
Resistenza Meccanica / Mechanical resistance / Résistance Mécanique / Resistencia mecanica / Mechanische Widerstandsfähigkeit	-
Accessori inclusi / Accessories included / Accessoires fournis / Accesorios incluidos / Zubehör enthalten	EASY CONNECTOR
Funzioni / Functions / Fonctions / Función / Funktionen	-
Dimensioni prodotto / Product dimensions / Dimensions du produit / Dimensiones producto / Abmessungen Produkt	Width x Height x Length: 240 x 77 x 218 mm
Dimensioni prodotto imballato / Packed dimensions / Dimensions du produit emballé / Dimensiones embalaje / Abmessungen Umverpackung	Width x Height x Length: 245 x 70 x 185 mm
Peso netto / Net Weight / Poids net / Peso neto / Gewicht netto	g
Peso prodotto imballato / Weight of packaged product / Poids du produit emballé / Peso producto con embalaje / Gewicht mit Umverpackung	g