

S1600-R

PRO series

Product Name: S1600-R

Product Number: 700S1600-R

Description

Rechargeable torch with 1600 and 120 lumens and sliding focus

Specifications

| | |
|---|---|
| Housing | Aluminium |
| Lens | Acrylic, optical |
| On/off switch | Bottom, red ABS |
| Battery type | 1 x 26650 - 4500mAh - 16.5Wh - Lithium rechargeable |
| Light source | 15W CREE XML2-U |
| Colour temperature (Kelvin) | 7500K |
| Focus | Sliding style optical focus system |
| Charger operating voltage | Required: 100V-240V, 50-60Hz |
| Charger output | Required: DC5V - 1A max (USB connector) |
| Output 30 seconds (lumen) | 120 (low beam) / 1600 (high beam) |
| Run time (hours) down to 1 lumen | 7 (low beam) / 5 (high beam) |
| Run time (hours) down to 10% of full lumens | 6.8 (low beam) / 4.5 (high beam) |
| Charging time (hours) | 6-8 |
| Charging level indicator | 1 x LED on torch |
| Beam distance (m) | 120 (low beam) / 400 (high beam) |
| Beam width (cm) from 1m distance | 160 (flood) / 12 (spot) |
| Protection class | IPX5 / IK07 / III (torch) - II (charger) |
| Operating temperature range (Celsius) | -20°C to +50°C |
| Charging port | Type C USB |
| Charging port cover | Turn-to-cover type C USB charging port |
| Cable for charger | 1 m (supplied in box). USB into charger, USB C into torch |



General Information

| | |
|-------------------------------|------------------|
| Torch weight (g) | 374 incl battery |
| Torch dimensions (cm) | ∅ 5.2 x 16.2 |
| EAN code box (1 pc) | 5703296701600 |
| EAN code inner carton/display | 5703296701617 |
| EAN code outer carton | 5703296701624 |
| Harmonized standard code | 8513100000 |

Packaging

| | |
|-----------------------|--------------------------------------|
| Description | "PRO" design printed box |
| Box size (cm) | 21.6 x 12.2 x 9.05 |
| Box weight (g) | N/A |
| Carton quantity (pcs) | 4 (inner carton) / 16 (outer carton) |
| Carton size (cm) | N/A |
| Carton weight (kg) | N/A |

Features

- Powerful torch with sliding focus
- Rechargeable. Hold head and turn tube for access to charging port.
- Charging indicator (1 x LED), red = charging / green = fully charged
- Switch mode: high-off-low-off
- Turn-to-cover USB C charging hole
- Supplied with pouch and lanyard
- Supplied with USB C cable for charger



Elwis Lighting A/S, Sandtoften 11, 2820 Gentofte, DK
www.elwislighting.com - Tel. +45 70 20 10 24

Version 1 09/2020
© Elwis Lighting 2020
All details without obligation